

YJ57083

Profibus DP Application



DESCRIPTION

22 AWG solid bare copper conductors, FHDPE insulation, overall Beldfoil® shielded plus tinned copper braid, overall PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	2
Nom. Conductor Stranding	1/0.65 mm
Nominal Conductor Gauge	22 AWG
Conductor Material	BC – Bare Copper

INSULATION:

Insulation Material	FHDPE – Foam High Density Polyethylene
Nom. Insulation Diameter	2.5 mm

OVERALL CABLING:

Overall Cabling Lay:	70 mm
Color Code Chart	1 Red 2 Green

OVERALL SHIELD:

Overall Shield Type & Material	Beldfoil® Al-Mylar Tape + Tinned Copper Braid
--------------------------------	---

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Nom. Outer Jacket Wall Thickness	1.0 mm

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	7.8 mm
--------------------------	--------

MECHANICAL CHARACTERISTICS:

Temperature Rating	- 20°C To + 70°C
Min. bending radius	15 x Cable Diameter

APPLICABLE SPECIFICATION AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

EU RoHS Compliant (Y/N)	Y
EU RoHS Compliance Date	June 2007

FLAME TEST:

Flame Test	IEC 60332-1
------------	-------------

Detailed Specifications & Technical Data



YJ57083

Profibus DP Application

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Conductor DC Resistance @ 20°C	16 Ω/kft
Nom. Capacitance Conductor to Conductor	8.5 pF/ft
Nom. Impedance (3MHz ~ 20MHz)	150+/-15 ohm
Nom. Velocity of Propagation	78 %
Max. Attenuation @ 0.2 MHz	1.10 dB/100mtr
Max. Attenuation @ 4 MHz	2.65 dB/100mtr
Max. Attenuation @ 16 MHz	5.40 dB/100mtr
Max. Operating Voltage	300 V

PUT-UPS AND COLORS:

Item	Description	Put-Up (M)	Ship Weight (kg)	Jacket Color
YJ57083 007500M	1 PR #22 FRFPE FRPE SH PVC	500	34	Violet
YJ57083 0071000M	1 PR #22 FRFPE FRPE SH PVC	1000	67	Violet
YJ57083 0071500M	1 PR #22 FRFPE FRPE SH PVC	1500	100	Violet

Revision Number: 1

Revision Date: 2013-03-05

©Copyright 2013 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.